



MEDIUM Fold Exclusive
mobile, big sized,
user-friendly!

Equipment

- One-piece frame consisting of high quality aluminium profile (see picture)
- Easy assembly and disassembly without tools
- Complete screen consists of only a few component parts
- Screen surface with approx. **10 cm** reinforcing black border for better image clarity
- Robust transport bag included in delivery standard
- Small packing size of only approx. 125 cm (length)
- Dimensions in accordance with international standards

Field of application

The MEDIUM Fold Exclusive screen is especially suitable for presentations in front of a large audience, on stage or at trade fairs. As the frame is a single part, it is quickly set up and component parts won't get lost. Therefore this screen is ideal for rental-services.

Installation

The screen is consisting of only four component parts: Folding frame, two fold-away stands (incl. thumbscrews) and projection surface. Installation as follows: Unfold aluminium frame, fix surface with push buttons onto front side of frame and mount fold-away stands with thumbscrews onto back of frame (adjustable height).

Technics

- Lightweight 32x32 mm aluminium profile
- Devilish solid snap joint locks allow easy assembly and disassembly
- Proven snap joints lock automatically and can be interfolded easily at a touch of a button (see picture)
- Low border of frame is height-adjustable from approx. 5 cm up to 140 cm (in increments of approx. 15 cm (see picture)
- Width/length of stands: approx. 103 cm (unfolded)

Accessory

- Wheeled case for convenient transport and safe storage (see picture)
- 2 wheels, space-saving stackable
 - Colour: grey
 - Material: Polyethylene



Surface

Front projection: 10 cm black border with push buttons
Type D, matt white, diffuse reflective

Material thickness:	approx. 0.22 mm
Base:	Vinyl-synthetic-material-foil
Grammage:	approx. 295 g/m ²
Web width:	approx. 210 cm
Back side:	grey, nearly opaque
Fire protection requirements:	B1, acc. to DIN 4102 part 1
Gain factor, DIN 19045:	approx. 1.02
Viewing angle, DIN 19045:	approx. +/- 50 degree
Features:	Uniform illumination, nearly no hot-spot

Rear projection: 10 cm black border with push buttons
Type R, diffuse

	Up to 214 cm (h/v) and from 306 cm image size	from 215 cm (h/v) and up to 305 cm image size
Material thickness:	approx. 0.28 mm	approx. 0.28 mm
Base:	Vinyl-synthetic-material-foil	Vinyl-synthetic-material-foil
Grammage:	approx. 370 g/m ²	approx. 380 g/m ²
Web width:	approx. 214 cm	approx. 305 cm
Colour of projection side:	Grey-green - translucent	grey - translucent
Fire protection requirements:	B1, acc. to DIN 4102 part 1	B1, acc. to DIN 4102 part 1
Gain factor, DIN 19045:	approx. 1.4	approx. 2.25
Viewing angle, DIN 19045:	approx. +/- 45 degree	approx. +/- 45 degree
Features:	Uniform illumination, nearly no hot-spot	Uniform illumination, nearly no hot-spot

Products

Code no. Front projection	Code no. Rear projection	External dimensions incl. 10 cm surrounding border W x H		Diagonal image size cm/inch	Weight net/gross
18518	18618	220 x 170 cm	7'3" x 5'2"	250/98	13/15 kg
18519	18619	264 x 203 cm	8'8" x 6'8"	305/120	17/19 kg
18528	18628	300 x 230 cm	9'10" x 7'7"	350/138	18/20 kg
18529	18629	325 x 249 cm	10'8" x 8'2"	381/150	20/22 kg
18531	18631	345 x 264 cm	11'4" x 8'8"	406/160	21/23 kg
18540	18640	406 x 310 cm	13'4" x 10'2"	483/190	24/26 kg
18521	18621	203 x 203 cm	6'8" x 6'8"	259/102	14/16 kg
18530	18630	294 x 294 cm	9' x 9'	388/153	16/18 kg
18467	Wheeled case, grey, 34 x 36 x 124 cm				10/10 kg

Screen will be delivered in cartons 30x30x130 cm each.



One-piece foldable frame



Snap joint



Back side



Wheeled case

Other formats and accessories are available on request.

All technical data and indications of format, weight, brightness or size are approximate.
Indications of weight are stated net.