

# Flexibility to teach or present from anywhere in the room

The StarBoard BT-2G is a lightweight graphics tablet that when connected to a projector and PC, enables presentations to be displayed on a large screen and the computer to be controlled remotely from anywhere in the room.



A cordless pen is used to annotate onto the tablet, which communicates wirelessly with an adaptor connected to the computer's USB port. Portable inspiration The StarBoard BT-2G tablet is ideal for use during a lesson, training session or meeting. By moving the pen across the surface of the tablet, the user can control the mouse movements of the PC. The pen facilitates both left and right mouse clicks, removing the need to use the PC directly.

Several tablets can be used in a session if desired, so that different people can interact with the computer when control is transferred to them. The new tablet features 12 function buttons, making it very simple to operate. Like all Hitachi interactive products, the new StarBoard BT-2G tablet is RoHS compliant (restriction of hazardous substances).

Wirelessly control your interactive presentation

**HITACHI**  
Inspire the Next

# The StarBoard BT-2G from Hitachi



## Technical Specifications

<b>Technology</b>	Electromagnetic
<b>Dimensions (mm)</b>	239mm (W) x 251mm (H) x 30mm (D)
<b>Active area</b>	6 x 4.5 inches (152 mm (W) x 114mm (H))
<b>Connection Interface</b> (Wireless/Wired)	Bluetooth 1.2 (class II)/USB 1.1 Full speed
<b>Connection Distance</b>	20 meters
<b>Input Methods</b>	Induction
<b>Resolution</b>	1000 Lpi
<b>Sampling Rate (Wireless/Wired)</b>	162 points/s/183 points/s
<b>Function button</b>	12 (Hold 1.5 seconds to work)
<b>Weight (without/with batteries)</b>	493g/545g
<b>Hot key</b>	1 (for Bluetooth unpairing)
<b>Power supply (Wireless)</b>	1.2V AA battery x 2 (Rechargeable battery suggested)
<b>(Wired)</b>	USB bus power (No batteries needed)
<b>Battery life</b>	Continual mode 24hrs
<b>Pen</b>	5V Pen
<b>Battery</b>	AAA battery x 1 (1.5V)
<b>Battery life</b>	Approximately 1800 hours
<b>Proximity</b>	8mm
Pen feature On/Off switch, 2 Side Buttons, Power Saving Mode, Low Battery Indicator LED	
<b>Operating Temperature</b>	0 - 40°C
<b>Operating Humidity</b>	20 - 80 %
<b>Safety Standard approvals</b>	CE, FCC
<b>Parallel usage</b>	Up to 7 devices per PC (Wireless mode)
<b>Warranty</b>	1 year
<b>Specification Items</b>	BTU02 (Class II) Standard
<b>Interface</b>	USB 2.0 (type A)
<b>RF Range</b>	Up to 40m (limited condition)
<b>Security</b>	Pairing, Encryption, Authentication
<b>Power</b>	USB bus power (LED indicator for checking power status)
<b>Dimensions (mm)</b>	58.5mm (W) x 17mm (H) x 8 mm (D)
<b>Weight</b>	6.8g

## System Requirements

<b>CPU</b>	Pentium II 300MHz (800MHz or faster recommended)
<b>RAM</b>	128MB (256MB or higher recommended)
<b>HDD</b>	200MB of free space

Windows Operating System Windows 2000, Windows XP  
(latest service pack recommended)

Further information:

**Hitachi Software Engineering (UK) Limited**  
Interactive Media Solutions Division  
Hillgate House, 26 Old Bailey,  
London EC4M 7HW, United Kingdom  
Tel: +44 (0)207 246 6868  
Fax: +44 (0)207 246 6860  
Email: sales@hitachi-software.co.uk

**Hitachi Software Engineering France S.A.S**  
Interactive Media Solutions Division  
7th Floor,  
64 rue du Dessous des Berges,  
75013 Paris, France  
Tel: +33 (0)153 827 600  
Fax: +33 (0)153 827 619  
Email: starboard@hitachisoft-eu.com

**Hitachi Software Engineering Europe A.G.**  
Interactive Media Solutions Division  
Kurfürstendamm 22,  
D-10719 Berlin, Germany  
Tel: +49 (0)30 8877 2600  
Fax: +49 (0)30 8877 2610  
Email: starboard@hitachisoft.de

[www.hitachisoft-eu.com](http://www.hitachisoft-eu.com)

**HITACHI**  
Inspire the Next